

## PRODUCTFICHE – FICHE PRODUIT - SPECIFICATION PRODUCT

### 1. Algemene informatie – Information général – General information

ARTIKELNR. AFNEMER / N° Art. Client / Ref. Customer	
ARTIKELNR. ACE / N° Art. ACE / Ref. ACE	SP02378
OMSCHRIJVING / Description / Description	Menuschaal alu 227x178x30mm 2 vaks R880G Ravier menu alu 227x178x30mm 2 comp R880G
DATUM / Date / Date	06/09/2022

### 2. Producteigenschappen – Caractéristiques - Specifications

MATERIAALSOORT/Matériel / Material	Aluminium	
INHOUD/ Contenance/ Content	2vakken – 2 compartiments	
GEWICHT / Poids / Weight	± 13.04 g / st - pc	
MAAT / Dimensions / Size	LENGTE / Longueur / Length	227 mm
	BREEDTE / Largeur / Width	178 mm
	HOOGTE / Hauteur / Height	30 mm
KLEUR / Couleur / Colour	Zilver - argenté	

### 3. Verpakkingswijze – Emballage- Packaging

AANTAL / Quantité / Quantity	1.000	Stuks – pièces – pieces	/ karton – carton - box
AANTAL / Quantité / Quantity	12	Dozen – cartons – boxes	/ pallet

## VERKLARING VAN OVEREENSTEMMING – DECLARATION DE CONFORMITE – DECLARATION OF CONFORMITY

---

The supplier established in the Community:

Name of the supplier: **Ace Packaging NV.**  
Complete address: **Industrieterrein 1/1 - IZ Webbekom 1013  
3290 Diest - Belgium**

declares that the product described above complies with the requirements:

### EU Regulations:

- **Regulation 1935/2004/EC**
- **Regulation 2023/2006/EC and subsequent updates and modifications**
- **Royal Decree of 17 February 2021 concerning metal and alloy materials and objects intended to come into contact with foodstuffs**

### Technical standards:

- **UNI EN 602:2007**
- **UNI EN 546-1:2007**
- **UNI EN 546-2:2007**
- **UNI EN 546-3:2007**
- **UNI EN 546-4:2007**
- **UNI EN 16773:2016**

in the following conditions of use:

- Type of food intended to come in contact with material/object:

### CONDITIONS OF USE:

The above mentioned products can be used for food contact at the following conditions:

- Short-term contact: less than 24 hours at any temperature conditions;
- Prolonged contact: more than 24 hours at refrigerated temperature;
- Prolonged contact: more than 24 hours at ambient temperature limited to the foods listed in Annex IV of M.D. 76/2007:
  - Cocoa and chocolate products
  - Coffee
  - Spices and herbs infusions
  - Sugar
  - Cereals and derived products
  - Dry pasta
  - Bakery products
  - Dried legumes and derived products
  - Dried fruit
  - Dried mushrooms
  - Dried vegetables
  - Confectionery products
  - Bakery products provided that the filling is not in direct contact with aluminum
- Not suitable for contact with strongly acid or heavily salted foods.

#### TEST CONDITIONS:

We declare that for the above described material no overall migration tests are foreseen and the material does not contain any substances with specific migration limit.

Release tests with tap water have been performed according to the test conditions considered by the Resolution CM/Res(2013)9 and showed positive results.

- Possible treatment of material/object:

The above described products can be used for cooking in:

- Traditional oven at the maximum temperature of 250°C (do not use at direct contact with open flames or electrical resistances)
- Industrial oven at the maximum temperature of 350°C up to 2 hours (do not use at direct contact with open flames or electrical resistances)
- Microwave oven at the maximum power for 15 minutes (only where indicated by the manufacturer)

The trays can be used at low temperatures (ambient temperature and/or refrigerated, including freezing and deep-freezing conditions).

#### DUAL USE ADDITIVES:

We declare that in the above described material there are no substances regulated by Regulation 1333/08/EC and/or Regulation 1334/08/EC (substances called “dual use” additives).

#### ALLERGENS:

In the supplied product, substances called allergens, as per Annex II of Regulation 1169/2011/EU and subsequent updates and modifications have not been intentionally added.

#### RAW MATERIALS:

The above material has been manufactured with degreased and pre-lubricated aluminum alloy. Chemical composition of aluminum laminate and its alloys is in compliance with technical standard UNI EN 602:2004 and aluminum has been manufactured in compliance with guideline UNI EN 16773:2016.

In the production of plain aluminum a lubricating oil has been used as processing aid. The oil complies with the requirements of M.D. 76/2007 and guideline UNI EN 16773:2016.

The lubricant does not contain G.M.O. substances and potentially allergenic substances.

- Shelf-life and material/object temperature

The ideal storage conditions are 15/20°C in a dry place and protected from the atmospheric elements

Traceability of the product is ensured according to Regulation (EC) No. 1935/2004

Our statements are based on the conformity documents made available by our suppliers, migration tests carried out by us or by a third party. It is the customers own responsibility to test the suitability

Done at, Diest 06/09/2022

Séverinne Valvekens

Quality department

i.o.v. Olivier Stappaerts (CEO Ace Packaging)



This document is valid until : 14/07/2025