

## PRODUCTFICHE – FICHE PRODUIT - SPECIFICATION PRODUCT

### 1. Algemene informatie – Information général – General information

|  |   |
|--|---|
| VORIG ARTIKELNR. ACE / N° Art. ACE précédent / Previous Ref. No. ACE |   |
| ARTIKELNR. ACE / N° Art. ACE / Ref. ACE                              | VA01123   |
| OMSCHRIJVING / Description / Description                             | Rol aluminium 11µ - Cbox / Rouleau aluminium 11µ - Cbox |
| DATUM / Date / Date  | 02/09/2022  |

### 2. Producteigenschappen – Caractéristiques - Specifications

|                                    |                            |                    |    |
|------------------------------------|----------------------------|--------------------|----|
| MATERIAALSOORT/Matériel / Material | Aluminium                  |                    |    |
| GEWICHT / Poids / Weight           | ± 1.92                     | kg / rol – rouleau |    |
| MAAT / Dimensions / Size           | LENGTE / Longueur / Length | 130                | m  |
|                                    | BREEDTE / Largeur / Width  | 450                | mm |
| WANDDIKTE / Epaisseur / Thickness  | 10.5                       | µm                 |    |
| KLEUR / Couleur / Colour           | Silver / Argent            |                    |    |

### 3. Verpakkingswijze – Emballage- Packaging

|                              |     |                         |                       |
|------------------------------|-----|-------------------------|-----------------------|
| AANTAL / Quantité / Quantity | 130 | Meter – mètres - meters | / Rol –rouleau - roll |
|------------------------------|-----|-------------------------|-----------------------|

### 4. Typische eigenschappen – Caractéristiques typiquement- Typical properties

| PROPRIETE                             | UNITE   | VALEUR             |
|---------------------------------------|---|--------------------|
| Diamètre intérieur mandrin            | mm  | 40,2               |
| Longueurs                             | ML  | 200                |
| Largeurs                              | cm  | 32.5               |
| Résistance à la traction              | Rm (N/mm <sup>2</sup> )                             | 80 – 110           |
| Résistance à la pression d'éclatement | Pe (kPa)  | >81                |
| Allongement                           | E50(%)  | >4.4               |
| Porosité                              | Pinholes m2   | <40                |
| Epaisseur                             | Mµ  | 10.5               |
| Densité                               | kg/dm <sup>2</sup>                                  | 2.70 – 2.74        |
| Coeff. Dilatation linéaire            | (°C-1)  | 23.3 – 24.4*10(-6) |
| Conductivité thermique                | W/m°C   | 223 – 239          |
| Capacité calorifique                  | J/g°C   | 0.88 – 0.95        |
| Résistivité                           | Ohm.m   | 27 – 37*10(-9)     |
| Température de fusion                 | °C  | 645 – 660          |
| Tolérances de fabrication             | Longueur +/- 4% - Largeur +/- 1% - Epaisseur +/- 5% |                    |

## VERKLARING VAN OVEREENSTEMMING – DECLARATION DE CONFORMITE – DECLARATION OF CONFORMITY

---

The supplier established in the Community:

Name of the supplier: **Ace Packaging NV.**

Complete address: **Industrieterrein 1/1 - IZ Webbekom 1013  
3290 Diest - Belgium**

declares that the product described above complies with the requirements of:

**Regulation EC 1935/2004 of 27th October 2004 (Framework Regulation)**

**Regulation EC 2023/2006 of 22th December 2006 ("GMP-regulation")**

**Belgian legislation: "Koninklijk Besluit van 11 mei 1992 - Arrête Royale du 11 mai 1992"**

**EN 602 Aluminium and aluminium alloys**

in the following conditions of use:

- Type of food intended to come in contact with material/object:

All food types, **except for** very acidic food (lemons, tomatoes,...) and very salty food (smoked salmon, ...)

- Possible treatment of material/object:

Suitable for cooking and reheating in the oven.

Food preservation: less than 24 hours under all temperature conditions, more than 24 hours at refrigeration temperature.

Do not put in contact with very acidic foods (lemon, tomato...) or highly salted foods (smoked salmon...).

Do not use in microwave oven.

**For containers and lids of aluminum overall & specific migration are not mandatory.**

- Shelf-life and material/object temperature:

The ideal storage conditions are 10/30°C in a dry place and protected from the atmospheric elements

Traceability of the product is ensured according to Regulation (EC) No. 1935/2004

Our statements are based on the conformity documents made available by our suppliers, migration tests carried out by us or by a third party. It is the customers own responsibility to test the suitability

Done at, Diest 02/09/2022

Nadja Louwet

Quality department

i.o.v. Olivier Stappaerts (CEO Ace Packaging)



This document is valid until 11.03.24